Collaboration between Networked Heterogeneous 3D Viewers through a PAC-C3D Modeling of the Shared Virtual Environment

Thierry Duval *
Université de Rennes 1, IRISA UMR CNRS 6074, Rennes, France

Cédric Fleury†
INSA de Rennes, IRISA UMR CNRS 6074, Rennes, France

Abstract

We propose to illustrate how the PAC-C3D software model makes it possible to share networked 3D Virtual Environments (VE) between heterogeneous 3D viewers written in Java3D and jReality.

Keywords: Software Architectural Models for CVE

Index Terms: H.5.2 [Information Interfaces and Presentation (e.g., HCI)]: User Interfaces—Theory and methods; I.3.7 [Computer Graphics]: 3-Dimensional Graphics and Realism—Virtual reality; D.2.11 [Software Engineering]: Software Architectures—Patterns

1 The PAC-C3D Model

We propose to design each object of a Collaborative Virtual Environment (CVE) according to the PAC-C3D model [1] illustrated figure 1. It is an explicit evolution of the PAC model dedicated to 3D CVE. On each user's computer, shared virtual objects of a CVE must be decomposed into three main kinds of components described by three interfaces. The *Abstraction* is in charge of the core data and behavior of the object, the *Presentations* are in charge of the virtual representation of the object to the user, and the *Control* is in charge of the consistency maintenance between *Abstraction* and *Presentations*, and between all the distributed *Controls* of the shared object.



Figure 1: Adaptation of the PAC model for 3D CVE

2 Viewing the same VE with different viewers

PAC makes it possible to design a VE with very small dependency to the 3D graphics API used for the 3D rendering: it proposes to confine all the graphics features of the virtual object in its *Presentation*. PAC-C3D proposes to use explicit interfaces components to strengthen this separation: it makes the *Control* components totally independent of the implementation of the *Presentation* components. The same 2D GUI and external interaction devices allow also to drive in a similar way these 3D viewers, as all the interaction and navigation orders are sent to *Control* and then to *Abstraction* components. We have used this model to design our IIVC [2] and three viewers based on Java3D, jReality and jMonkey.

*e-mail: thierry.duval@irisa.fr
†e-mail: cedric.fleury@irisa.fr



Figure 2: Two different viewers sharing the same virtual environment

3 Sharing the same VE between different viewers

PAC-C3D allows these different 3D viewers to share the same 3D VE at run-time (see figure 2) over a network. PAC-C3D proposes to put all the collaborative features (distribution, synchronization, etc.) in the *Control* components, ensuring that each evolution of a virtual object is distributed to the other *Control* components of this virtual object, according to their distribution policy [3].

4 Enriching 3D viewers inter-operability

It is possible to enrich the interaction possibilities of a viewer *X* with extra functions provided by an other viewer *Y*. It consists in allowing the viewer *X* to control a virtual object provided by the viewer *Y*. The viewer *X* owns a local *Control* of this object, so each order given to this local *Control* by the viewer *X* will be forwarded to the *Control* of the object on the viewer *Y* that will forward it to its *Abstraction*. To be more efficient, the distribution policy of this virtual object can be changed dynamically at run-time. For example, the *Referent Control* can be migrated to the same process than the viewer *Y*. These exchanges between different viewers strengthen their inter-operability.

5 Conclusion

PAC-C3D makes it possible to design a CVE with very small dependency on a 3D graphics API, and it makes it easy to use different 3D graphics API on different remote computers sharing the same collaborative session, providing easy inter-operability between 3D graphics API such as Java3D, jReality and jMonkey.

Acknowledgements

This work was partly funded by the French Research National Agency project named Collaviz (ANR-08-COSI-003-01).

References

[1] T. Duval and C. Fleury. PAC-C3D: A New Software Architectural Model for Designing 3D Collaborative Virtual Environments. In *Proc. of ICAT*, page to Appear, 2011.

[2] C. Fleury, A. Chauffaut, T. Duval, V. Gouranton, and B. Arnaldi. A Generic Model for Embedding Users' Physical Workspaces into Multi-Scale Collaborative Virtual Environments. In *Proc. of ICAT*, pages 1–8, 2010.

[3] C. Fleury, T. Duval, V. Gouranton, and B. Arnaldi. A New Adaptive Data Distribution Model for Consistency Maintenance in Collaborative Virtual Environments. In *Proc. of JVRC*, pages 29–36, 2010.