

public key initialisation

Protocol Purpose

Mutual Authentication with Public Key initialisation (in case the Authentication Server and Client don't share a key)

Definition Reference

Kcg : symmetric_key,
T1start : text,
T1expire : text,
Ktemp : symmetric_key

```

Kcg      : symmetric_key,
Kcs      : symmetric_key,
T1start, T1expire : text,
T2start, T2expire : text,
T1       : text

```

```
const sec_t_Kcg, sec_t_Kcs : protocol_id
```

```
init State := 21
```

```
transition
```

```

1. State = 21 /\ RCV( S.N2' .
                    {U' . C. G. Kcg' . T1start' . T1expire' }_Kag.
                    {C. T1' }_Kcg' )
                    /\ not(in(T1' , L)) =>
State' := 22 /\ Kcs' := new()
                /\ T2start' := new()
                /\ T2expire' := new()
                /\ SND( U' .
                    {U' . C. S. Kcs' . T2start' . T2expire' }_Kgs.
                    {S. Kcs' . T2start' . T2expire' . N2' }_Kcg'
                    )
                /\ L' := cons(T1' , L)
                /\ wrequest(G, C, t1, T1' )
                /\ witness(G, C, n2, N2' )
                /\ secret(Kcg' , sec_t_Kcg, {A, C, G})
                /\ secret(Kcs' , sec_t_Kcs, {G, C, S})

```

```
end role
```

```

role server( S, C, G      : agent,
              Kgs      : symmetric_key,
              SND, RCV : channel -514(RC)1Kag.

```


U : text,

end role